

# CALLON

## SOLID TYRES FOR FORKLIFTS

- ✓ **COMPREHENSIVE QUALITY WARRANTY POLICY WITH RELIABLE FACTORY BACK UP**
- ✓ **NATURAL RUBBER BASED COMPOUND**
- ✓ **AVAILABLE IN TWO TREAD PATTERNS**
- ✓ **THREE STAGE CONSTRUCTION**
- ✓ **VALUE FOR MONEY**
- ✓ **HIGH RELIABILITY**



## SOLID TYRES STANDARD : AVAILABLE SIZES

Size	Rim Type	Tread Pattern	Weight (KG)	Dimensions(MM.)		Maximum Loading									
						Forklift (Counter balanced)						Industrial Vehicles			
						10KM/H		16KM/H		25KM/H					
				O.D.	Width of Profile	Driving Wheel	Steering Wheel	Driving Wheel	Steering Wheel	Driving Wheel	Steering Wheel	Rest Loading	6KM/H	10KM/H	25KM/H
4.00-8/2.50	2.50C-8	D	9.4	390	100	910	700	830	640	765	590	885	765	695	590
4.00-8/3.00	3.00D-8	A	10.5	402	110	1090	840	995	765	925	710	1065	925	840	710
4.00-8/3.75	3.75-8	D	13.7	408	126	1240	990	1195	865	1110	835	1255	1150	985	835
5.00-8/3.00	3.00D-8	C,E	15.9	450	124	1255	965	1145	880	1060	815	1225	1060	960	815
5.00-8/3.50	3.50-8	C	16.5	449	125	1255	965	1145	880	1060	815	1225	1060	960	815
6.00-9/4.00	4.00E-9	C,E,F	25.1	518	147	1975	1520	1805	1390	1675	1290	1935	1675	1520	1290
6.50-10/5.00	5.00F-10	C,E,F	33.6	558	158	2715	2090	2485	1910	2310	1775	2665	2310	2095	1775
7.00-12/5.00	5.00S-12	C,E,F	45.7	642	180	3105	2390	2835	2180	2635	2025	3040	2635	2390	2025
8.25-12/5.00	5.00S-12	C,E	65.0	706	201	3425	2635	3125	2405	2905	2235	3355	2905	2635	2235
7.00-15/5.50	5.5-15	A,C	52.7	689	200	3700	2845	3375	2595	3135	2410	3615	3135	2845	2410
7.50-15/5.50	5.5-15	C	68.0	739	210	3805	2925	3470	2670	3225	2480	3720	3225	2925	2480
7.50-15/6.00	6.0-15	C	68.0	739	210	4145	3190	3785	2910	3510	2700	4050	3510	3185	2700
7.50-15/6.50	6.5-15	C	68.5	739	210	4490	3455	4100	3155	3810	2930	4395	3810	3455	2930
8.25-15/5.50	5.50-15	C	81.1	784	204	4305	3310	3925	3020	3640	2800	4200	3640	3305	2800
8.25-15/6.50	6.5-15	C,E,F	85.2	794	209	5085	3910	4640	3570	4310	3315	4975	4310	3910	3315
7.50-16/5.50	5.50F-16	C	83.5	785	214	4035	3105	3685	2835	3425	2635	3955	3425	3110	2635
7.50-16/6.00	6.00G-16	C	83.5	785	214	4400	3385	4025	3095	3730	2870	4305	3730	3385	2870
7.50-16/6.50	6.50H-16	C	83.5	785	214	4770	3670	4355	3350	4045	3110	4665	4045	3670	3110
8.25-20/6.50	6.50-20	C	110.0	940	226	5165	4305	4715	3930	4380	3650	5475	4745	3980	3650
8.25-20/7.00	7.0-20	C	110.5	940	226	5335	4445	4870	4060	4525	3770	5655	4900	4110	3770
18x7-8/4.33	4.33R-8	C,E	20.4	443	163	2430	1870	2215	1705	2060	1585	2375	2060	1870	1585
21x8-9/6.00	6.00E-09	A	34.3	519	190	2890	2225	2645	2035	2455	1890	2835	2455	2230	1890
28x9-15/7.0	7.0-15	C,E,F	61.2	693	215	4060	3125	3710	2855	3445	2650	3975	3445	3125	2650
250-15/7.0	7.0-15	A	76.2	722	239	5220	4015	4770	3670	4425	3405	5105	4425	4015	3405
250-15/7.5	7.5-15	A	76.2	722	239	5595	4305	5110	3930	4745	2650	5475	4745	4305	3650
300-15/8.0	8.0-15	C	118.2	820	272	6895	5305	6300	4845	5850	4500	6750	5850	5310	4500

\*28x9-15/7.0 = 8.15-15/7.0

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

## TREAD PATTERNS

### Sold Tyres Standard


TYPE C



TYPE F



### Non-Marking Tyres



## NON-MARKING TYRES : AVAILABLE SIZES

Size	Rim Type	Tread Pattern	Weight (KG)	Dimensions(MM.)		Maximum Loading									
						Forklift (Counter balanced)						Industrial Vehicles			
						10KM/H		16KM/H		25KM/H					
				O.D.	Width of Profile	Driving Wheel	Steering Wheel	Driving Wheel	Steering Wheel	Driving Wheel	Steering Wheel	Rest Loading	6KM/H	10KM/H	25KM/H
4.00-8/2.50	2.50C-8	D	9.4	390	100	910	700	830	640	765	590	885	765	695	590
4.00-8/3.00	3.00D-8	A	10.5	402	110	1090	840	995	765	925	710	1065	925	840	710
4.00-8/3.75	3.75-8	D	13.7	408	126	1240	990	1195	865	1110	835	1255	1150	985	835
5.00-8/3.00	3.00D-8	C,E	15.9	450	124	1255	965	1145	880	1060	815	1225	1060	960	815
5.00-8/3.50	3.50-8	C	16.5	449	125	1255	965	1145	880	1060	815	1225	1060	960	815
6.00-9/4.00	4.00E-9	C,E,F	25.1	518	147	1975	1520	1805	1390	1675	1290	1935	1675	1520	1290
6.50-10/5.00	5.00F-10	C,E,F	33.6	558	158	2715	2090	2485	1910	2310	1775	2665	2310	2095	1775
7.00-12/5.00	5.00S-12	C,E,F	45.7	642	180	3105	2390	2835	2180	2635	2025	3040	2635	2390	2025
7.00-15/5.50	5.5-15	A,C	52.7	689	200	3700	2845	3375	2595	3135	2410	3615	3135	2845	2410
7.50-15/5.50	5.5-15	C	68.0	739	210	3805	2925	3470	2670	3225	2480	3720	3225	2925	2480
7.50-15/6.00	6.0-15	C	68.0	739	210	4145	3190	3785	2910	3510	2700	4050	3510	3185	2700
7.50-15/6.50	6.5-15	C	68.5	739	210	4490	3455	4100	3155	3810	2930	4395	3810	3455	2930
8.25-15/6.50	6.5-15	C,E,F	85.2	794	209	5085	3910	4640	3570	4310	3315	4975	4310	3910	3315
7.50-16/5.50	5.50F-16	C	83.5	785	214	4035	3105	3685	2835	3425	2635	3955	3425	3110	2635
7.50-16/6.00	6.00G-16	C	83.5	785	214	4400	3385	4025	3095	3730	2870	4305	3730	3385	2870
7.50-16/6.50	6.50H-16	C	83.5	785	214	4770	3670	4355	3350	4045	3110	4665	4045	3670	3110
18x7-8/4.33	4.33R-8	C,E	20.4	443	163	2430	1870	2215	1705	2060	1585	2375	2060	1870	1585
21x8-9/6.00	6.00E-09	A	34.3	519	190	2890	2225	2645	2035	2455	1890	2835	2455	2230	1890
28x9-15/7.0	7.0-15	C,E,F	61.2	693	215	4060	3125	3710	2855	3445	2650	3975	3445	3125	2650
250-15/7.0	7.0-15	A	76.2	722	239	5220	4015	4770	3670	4425	3405	5105	4425	4015	3405
250-15/7.5	7.5-15	A	76.2	722	239	5595	4305	5110	3930	4745	2650	5475	4745	4305	3650
300-15/8.0	8.0-15	C	118.2	820	272	6895	5305	6300	4845	5850	4500	6750	5850	5310	4500


\*28x9-15/7.0 = 8.15-15/7.0

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

DISTRIBUTED BY :

## SKID STEER LOADER TYRES : AVAILABLE SIZES

Size	Rim Type	Dimensions (MM.)		Maximum Loading (KG)		Other Industrial Vehicles
		O.D.	Width of Profile	10KM/H	16KM/H	16KM/H
31x6x10	10-16.5	783	252	5627	4977	4328
33x6x11	12-16.5	834	264	6354	5621	4887



SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE